

BT-THEATRE HD 1

06018

DESCRIPTION

A powerful "ALL-IN-1" LED theater spot with motorized 14°~55° zoom with perfect white (CRI>90Ra) & endless color pallet

FEATURES

- A powerful "ALL-IN-1" LED theater spot with motorized 14° ~ 55° zoom.
- No more need for separate white and color projectors, BT-THEATRE HD1 does it all:
 - Perfect WHITE with high CRI > 90Ra and CCT presets
 - Rich COLOR selection with color presets!
- Different CCT presets for white: ..., 2700K, ..., 3000K, 3200K, ..., 4000K, ..., 5600K, ...
- Different color presets (LEE® / ROSCO® numbering)
- Based on a 200watt 5-color RGBAL-LED (**R**ed, **G**reen, **B**lue, **A**mber, **L**ime)
- Very silent operation: heat-pipe technology with low noise cooling fan and different presets (live, studio, ...)
- DMX-controlled: 4 different channel modes for maximum flexibility
- RDM-functionality for easy remote setup: DMX addressing, channel mode, ...
- Flicker free TV-recordings thanks to the adjustable high LED-refresh rate!
- Four dimmer settings with different behavior & speed.
- Manual control for dimming, colors, CCT & zoom.
- OLED-display to navigate easily through the setup menu!
- In case of DMX failure you can choose between blackout and freeze mode.
- Lock function to avoid unwanted altering of the settings.
- Rugged extruded aluminum housing.
- 3 & 5pin DMX in/outputs + PowerCON in/outputs for easy daisy chaining.
- A four-leaf barndoor (BT-THEATRE BARN2) is optionally available.






www.briteq-lighting.com | <https://www.facebook.com/Briteq>

Beglec NV has the right to change products and specifications with and without notice. Major as well as minor changes can be involved. This leaflet can contain errors, therefore we advice to consult your local dealer to ensure that actual features and specifications match your requirements. Copyright © 2018 by BEGLEC NV. All rights reserved.



TECHNICAL SPECIFICATIONS

General : Application	Stage & Rental, Theatre
General : Dimensions (cm)	45 x 29 x 26
General : Weight (kg)	7.56
General : Powerinput	AC 100 - 240V, 50/60Hz
General : Energy Label	No
General : Power consumption W	240
General : Color	black
General : Display	OLED
General : Fixation	optional standard clamp
General : IP rating	indoor
Control : manual	Yes
Control : Master/Slave	No
Control : SMART-DMX	No
Control : Standalone	fixed
Control : programmable	No
Control : upgradable software	Yes
Control : maximum DMX channels	19
Light : lamp socket	none
Light : Lux	1428
Light : lamp	LED
Light : min. color temperature (K)	1800
Light : max. color temperature (K)	8000
Light : CRI	90
Light : colors	RGBAL
Light : mix colors	Yes
Light : focus	No
Light : zoom	Motorized
Light : iris	No
Light : frost filter	No
Light : min. beam angle (°)	14
Light : max. beam angle (°)	55
Light : min. refresh rate (kHz)	0.6
Light : max. refresh rate (kHz)	25
Connections : input	3 pin XLR, 5 pin XLR, powercon, rdm
Connections : output	3 pin XLR, 5 pin XLR, powercon, rdm
Brand	BRITEQ
EANCode	5420025660181
Discontinued	No



www.briteq-lighting.com | <https://www.facebook.com/Briteq>

Beglec NV has the right to change products and specifications with and without notice. Major as well as minor changes can be involved. This leaflet can contain errors, therefore we advice to consult your local dealer to ensure that actual features and specifications match your requirements. Copyright © 2018 by BEGLEC NV. All rights reserved.