

DigiStrip IP100

100 cm IP65 outdoor LED video pixel strip with 10 mm pixel pitch

ORDER CODE: **DIGISTRIP100**



DigiStrip IP100 is a linear LED 10 mm pixel pitch video fixture for the rental market with an extensive range of optical accessories for a wide variety of looks (black and white and transparent). Each 1 meter long strip features 100 RGB / FC LEDs with individual pixel control and a 100° viewing angle. The mechanics of **DigiStrip IP100** have been studied to grant greater mounting flexibility by adding sliding hardware on the back for truss application and on the side for multiple vertical linking. The external control unit **DigiDriver IP** is compatible with Art-Net and Kling-Net protocol and runs both signal and power over a 4 pole cable that provides greater stability and connection in a daisy chain (up to 20 **DigiStrip IP100**)

MAIN FEATURES

- High-resolution IP65 rated video pixel batten, featuring 100 LEDs in a row
- Several optional optical filters delivering a wide range of different looks and finishes
- Easy setup and wiring through the DigiDriver IP

TECHNICAL SPECIFICATION

LIGHT SOURCE

- Source: 100x0,25W RGB LEDs
- Luminous flux: without cover: 542 lm - black cover: 81 lm - flat white cover: 319 lm - dome white cover: 351lm @full
- Lux: without cover: 7 lx - black cover: 1 lx - flat white cover: 3 lx - dome white cover: 2lx @5 m full
- Other: view angle 100° - driver chip MBI 5043
- Source life expectancy: > 50.000 h

OPTICS

- Pixel pitch: 10mm
- Additional optics: black cover and white dome cover (included)
- Other: flat white cover (included)

COLOUR SYSTEM

- Colour mixing: RGB / FC

BODY

- Hardware on-board: on board mechanics for modular assembly of multiple fixtures
- Body: sturdy aluminum profile
- Body colour: white optic and body black

CONTROL

- Control units: 20 pcs power & signal under 1 pc DIGIDRIVERIP
- Art-Net channels: 300ch
- Protocols: Art-Net, Kling-Net, sACN
- Pixel control: pixel2pixel control

ELECTRICAL

- Mains power supply: DC 48V
- Max power consumption: 25W

PHYSICAL


- IP rating: 65 for temporary outdoor application, not for fixed installation
- Suspension and fixing: bracket for truss rigging and hardware for connection of more units
- Signal connection: Seetronic XLR 4p IN/OUT connectors
- Dimensions (WxHxD): 1.000x36x128mm
- Weight: 2,7kg

ACCESSORIES & RELATED PRODUCTS

- | | | | |
|------------|---|----------------|---|
| ▪ C6002B | Slim aluminum clamp, 200kg loading, 48-51mm tubes, M10 bolt, Black | ▪ DIGIDRIVERIP | Master driver for Digi IP series, Art-Net, Kling-Net, IP65, 550W, |
| ▪ RSR0630B | Steel security cable for hanging bodies, inox steel shackle, L=60 cm, black | ▪ DIGILINKIP | Digi IP series signal 4-pin cable |


**PRESET FULL ON
(WITHOUT COVER)**

Beam angle 50%: 123,7°




**PRESET FULL ON
(FLAT COVER)**

Beam angle 50%: 136,8°



TECHNICAL DRAWINGS



For more product info and downloads visit our website

